

ROAD RACING and SUPERMOTO RANGE 2025

METZELER SHARING INDEPENDENCE		RIM recommended (inches)	WIDTH mm (inches)	DIAMETER centre mm (inches)	DIAMETER shoulder mm (inches)	WEIGHT kgs (lbs/pound)	COLD PRESSURE recommended range (w/o warmers) bar (psi)	HOT PRESSURE recommended range (after warmers) bar (psi)	WARMERS usage °C (°F)	
RACETEC RR SLICK										
D R Y	17"	<i>front 120/70 R17</i>	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.1/2.2 (30/32)	2.2/2.5 (32/36)	50 mins. @ 80°C (176°F)
		<i>front 125/70 R17</i>	3.50	124 (4.88)	610 (24.02)	508 (20.00)	4.3 (9.5)	2.1/2.2 (30/32)	2.2/2.5 (32/36)	
		<i>rear 180/60 R17</i>	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 190/60 R17</i>	5.50	195 (7.68)	662 (26.06)	530 (20.87)	6.6 (14.6)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 200/60 R17</i>	6.00	200 (7.87)	662 (26.06)	530 (20.87)	6.7 (14.7)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 200/65 R17</i>	6.00	202 (7.95)	672 (26.45)	530 (20.87)	6.8 (14.9)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
RACETEC TD SLICK										
S L I C K	17"	<i>front 120/70 R17</i>	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.1/2.2 (30/32)	2.2/2.5 (32/36)	50 mins. @ 80°C (176°F)
		<i>rear 180/55 ZR17</i>	5.50	181 (7.12)	641 (25.23)	529 (20.83)	5.8 (12.8)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 180/60 ZR17</i>	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 190/55 ZR17</i>	5.50 - 6.00	191 (7.51)	652 (25.67)	527 (20.75)	6.2 (13.7)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 200/55 R17</i>	6.00	193 (7.60)	656 (25.83)	531 (20.90)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
RACETEC SM										
R A I N	16.5"	<i>front 125/75 R420</i>	3.50	120 (4.72)	600 (23.62)	489 (19.25)	4.4 (9.7)	1.6/1.8 (23/26)	1.8/1.9 (26/28)	40 mins. @ 80°C (176°F)
		<i>front 125/75 R17</i>	3.50	120 (4.72)	604 (23.77)	499 (19.64)	4.3 (9.5)	1.6/1.8 (23/26)	1.8/1.9 (26/28)	
		<i>rear 165/55 R17</i>	5.00 - 5.50	162 (6.38)	631 (24.84)	521 (20.51)	5.4 (11.9)	1.5/1.6 (22/23)	1.6/1.7 (23/25)	
RACETEC SM RAIN										
R A I N	16.5"	<i>front 125/75 R420</i>	3.50	120 (4.72)	600 (23.62)	489 (19.25)	4.4 (9.7)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)
		<i>front 125/75 R17</i>	3.50	120 (4.72)	604 (23.77)	499 (19.64)	4.3 (9.5)	2.3 (34)	2.4 (35)	
		<i>rear 165/55 R17</i>	5.50	162 (6.38)	631 (24.84)	521 (20.51)	5.6 (12.3)	1.9 (28)	2.0 (29)	
RACETEC RR										
D R Y	17"	<i>front 120/70 ZR17</i>	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.0/2.2 (29/32)	2.1/2.4 (30/35)	50 mins. @ 80°C (176°F)
		<i>rear 160/60 ZR17</i>	4.50 - 5.00	165 (6.50)	631 (24.84)	521 (20.51)	5.6 (12.4)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 180/55 ZR17</i>	5.50	181 (7.12)	641 (25.23)	529 (20.83)	5.8 (12.8)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 180/60 ZR17</i>	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 190/55 ZR17</i>	5.50 - 6.00	191 (7.51)	652 (25.67)	527 (20.75)	6.2 (13.7)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
		<i>rear 200/55 ZR17</i>	6.00	200 (7.87)	662 (26.06)	530 (20.87)	6.7 (14.7)	1.6/1.8 (23/26)	1.7/1.9 (25/28)	
	18"	<i>front 110/80 ZR18</i>	2.50 - 3.00	114 (4.49)	632 (24.88)	545 (21.45)	4.8 (10.5)	2.0/2.2 (29/32)	2.1/2.4 (30/35)	
		<i>rear 130/80 ZR18</i>	3.00 - 3.50	129 (5.01)	670 (26.38)	577 (22.72)	5.3 (11.7)	1.7/1.9 (25/28)	1.8/2.0 (26/29)	
RACETEC RR INTERMEDIATE										
I N T E R	17"	<i>front 120/70 R17</i>	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.2 (9.3)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)
		<i>rear 190/60 R17</i>	5.50 - 6.00	193 (7.60)	656 (25.83)	531 (20.90)	6.7 (14.8)	1.9 (28)	2.0 (29)	
RACETEC RR RAIN										
R A I N	17"	<i>front 120/70 R17</i>	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)
		<i>rear 190/60 R17</i>	5.50 - 6.00	193 (7.60)	656 (25.83)	531 (20.90)	7.1 (15.6)	1.9 (28)	2.0 (29)	